

..... safety, durability and reliability!!

MIDI RECYCLING SYSTEM HDD JBR90



MIDI RECYCLING SYSTEM HDD JBR90

Meerkat PT 3 mtrs shaker

header distribution box 380-415V/ 50Hz/3 phase
single deck angle adjustment - +3°, -3°
gross screen deck area 2.1m² (22.5ft²)
total screen non-blanked area (API) 1.5m² (15.9ft²)
2 x 1,5 KW linear motion and 1 x 0,45 KW elliptical motion
motion type = 6.3G Linear; 5.2G balanced elliptical
vibration speed = 1500 RPM (50 Hz Power Supply)
wedge lock screen tensioners hold four (4) composite
Dimension & weight: 2,35x1,75x1,35 mt 2235 kgs



Transfer Pump QS15-22 Centrifugal

Power supply V/Hz 400/50
Input power kW 15
Max pressure bar 2,5
Max delivery 2500 lpm
Outlet port mm (") 100 (4)
Suction support mm (") 100 (4)
Dimension & weight: 1,50x1,32x0,45 mt 300 kgs



5 m³ steel tank

steel frame made with steel tank 4 mm
bottom tank steel 5 mm
gross volume tank 6 m³
n. 1 bottom discharge valve
n. 2 front VITAULIC 6" with flange connection inlet-outlet
painting epoxy primer + polyurethane enamel
colour: RAL 9002
Dimension & weight: 3,15x1,60x1,60 mt 1270 kgs



MUD RECYCLING SYSTEM HDD JBR150

